

ESCALERA PLATAFORMA/RETRÁCTIL



Uso Industrial:

136 kg.


FIBRA DE VIDRIO



ESCALERA CERRADA



ESCALERA ABIERTA



ESPECIFICACIONES			DIMENSIONES (METROS)				
PASOS	PESO	CAPACIDAD DE CARGA	LONGITUD ESCALERA (A)	ANCHO MÁXIMO (B)	APERTURA (C)	ALTURA DE PLATAFORMA (D)	ALTURA MÁXIMA (E)
2	-	136 kg	1.64	0.59	0.74	0.57	1.40
3	-	136kg	1.94	0.62	0.62	0.85	1.70
4	-	136 kg	2.24	0.65	0.65	1.13	2.02
5	-	136 kg	2.54	0.68	0.68	1.42	2.31
6	-	136 kg	2.85	0.71	0.71	1.72	2.62
7	-	136kg	3.15	0.74	0.74	2.01	2.94
8	-	136 kg	3.45	0.77	0.77	2.39	3.20
9	-	136 kg	3.75	0.80	0.80	2.57	3.49
10	-	136 kg	4.05	0.83	0.83	2.85	3.79
11	-	136 kg	4.36	0.86	0.86	3.13	4.10
12	-	136 kg	4.66	0.89	0.89	3.41	4.31
13	-	136 kg	4.96	0.92	0.92	3.69	4.60
14	-	136 kg	5.26	0.95	0.95	3.97	4.93
15	-	136 kg	5.57	0.98	0.98	4.25	5.25
16	-	136 kg	5.87	1.01	1.01	4.53	5.57
17	-	136 kg	6.17	1.04	1.04	4.81	5.90

Ficha técnica



Tapa completa de aluminio reforzado




Peldaños con superficie antideslizantes



Tirantes separadores antipélico



Refuerzos en las cuatro patas



Zapatas de aluminio reforzadas con jébe antideslizantes



Agarraderas de mano de seguridad

CERTIFICACIONES:

